

BMSY 440 CGH - BMSY 360 CGH


Semi Automatic Mitre Cutting Bandsaw Machine

Standards

- Planetary Gearbox
- Linear Way
- Hydraumechanical Blade Tension
- Synchronization Moveable Arm/Vice
- Chip Brush
- Digital Angle Display
- Inverter
- Control Panel
- Sensitive Pressure
- Hydraulic Angle Fixing
- Blade 41
- SAP Coolant Pump
- Security Switch
- Optical Quick Approaching
- 3° Inclined Bow
- Hydraulic Vice
- Synchronization Moveable Arm/Vice
- Blade 34

Optionals

- Microspray Coolant
- Hydraulic Blade Tension
- Laser Pointer
- 3 Mt Motorized Roller Table
- 3 Mt Roller Table
- Chip Conveyor
- Hydraulic Top Clamping



OPTIONALS	Microspray Coolant	Hydraulic Blade Tension	Laser Pointer	3 Mt Motorized Roller Table	3 Mt Roller Table	Chip Conveyor	Hydraulic Top Clamping

Technical Datas

	BMSY 440 CGH				BMSY 360 CGH			
Cutting Capacity	0°	450	695 x 425	425	0°	360	700 x 360	360
	30°	450	560 x 425	425	30°	360	590 x 360	360
	45°	430	430x 425	425	45°	360	450 x 360	360
	60°	320	260 x 425	290	60°	325	280 x 360	290
Main Motor	4 kW				3 kW			
Hydraulic Motor	0,55 kW				0,55 kW			
Coolant Motor	0,12 kW				0,12 kW			
Cutting Speeds	20 - 100 m/min				20 - 100 m/min			
Blade Size	5400 x 41 x 1,3 mm				5200 x 34 x 1,1 mm			
Working Height	690 mm				690 mm			
Dimensions	Lenght 2850 mm		Height 1800 mm		Lenght 2850 mm		Height 1820 mm	
	Width 1300 mm		Weight 1630 kg		Width 1300 mm		Weight 1460 kg	

