



3 jaw self centering chuck 4 jaw independent chuck

Face plate
Steady rest
Follow rest
Chuck cover
4 station tool

Halogen working lamp Threading chasing dial Full length splash guard Reduction sleeve Dead centers

4 station tool post Operating tool kit with tools

Foot brake Operation manual

Dist. Between centres:	1000/1500	Lead screw thre
Swing over bed:	510mm	Long Feed Ran
Swing over cross slide:	305mm	Cross Feed Rar
Swing in gap:	735	Thread Pitch M
Length of gap:	170mm	Thread Pitch In
Bed width:	350mm	Thread Pitch D
Spindle nose:	DI-8	Thread Pitch M
Spindle bore:	80mm	Quill Ø:
Taper of spindle bore:	MT 7	Quill Travel:
Spindle speed Range:	12 Changes, 25-2000 r/min	Quill Taper:
Compound rest travel:	130mm	Mail Motor:
Cross slide travel:	316mm	Dimensions:
Max. tool section:	25x25mm	Weight:

Lead screw thread:	6mm / 4TPI
Long Feed Range:	35 kinds, 0.059-1.646 mm/rev
Cross Feed Range:	42 kinds, 0.020-0.573 mm/rev
Thread Pitch Metric:	47 kinds, 0.2-14mm
Thread Pitch Imperial:	60 kinds, 2-112 TPI
Thread Pitch Diameter:	50 kinds, 4-112 TPI
Thread Pitch Module:	34 kinds, 0.1-7MP
Quill Ø:	75mm
Quill Travel:	180mm
Quill Taper:	MT 5
Mail Motor:	7.5kW
Dimensions:	2840x1150x1430 mm
Weight:	2550/2840kg



Centre Lathe
Turning Centre