### **NC Hydraulic Swing-Beam Guillotine**

### **QC12Y MODELS AVAILABLE**



#### **FEATURES:**

- Estun E21-S with hang type control-arm Automatic motorised backstop, running on ball screws with linear guides Manual gap adjustment Shadow cutting line Heavy duty foot pedal with emergency stops Table rollers for smooth material handling
- Rear safety guards & slider plates for material ejection Single and continuous stroke movement Front blade guards with safety micro switches Side squaring arm and front supports with flip over stops with squaring discs.

	QC12Y- 4×2500	QC12Y- 4×3200	QC12Y- 4×4000	QC12Y- 6×2500	QC12Y- 6×3200	QC12Y- 6×4000	QC12Y- 6×6000	QC12Y- 8×2500	QC12Y- 8×3200	QC12Y- 8×4000	QC12Y- 8×5000	QC12Y- 8×6000
Model	4×2500	4×3200	4×4000	6×2500	6×3200	6×4000	6×6000	8×2500	8×3200	8×4000	8×5000	8×6000
Shearing Angle	1°30′	1°30′	1°30′	1°30′	1°30′	1°30′	1°30′	1°30′	1°30′	1°30′	1°30′	1°16′
Strokes p/m	≥20	≥16	≥12	≥24	≥20	≥14	≥8	≥24	≥20	≥16	≥8	≥6
Backgauge adj.	20-600	20-600	20-600	20-600	20-600	20-800	20-800	20-600	20-600	20-600	20-800	20-800
Throat	85	85	85	145	145	145	140	145	145	145	145	145
Motor	5.5	5.5	5.5	11	11	11	15	15	15	15	15	15
Weight	3460	4280	6900	4685	6060	8520	17000	5800	7360	9460	18000	21800
Dimension	3100× 1430× 1450	3800× 1555× 1500	4600× 1705× 1600	3150× 1500× 1600	3850× 1600× 1620	4650× 1850× 1700	6710× 2250× 2100	3180× 1680× 1700	3880× 1830× 1720	4680× 1980× 1780	5855× 2260× 2100	6880× 2260× 2100



# **NC Hydraulic Swing-Beam Guillotine**

## QC12Y MODELS AVAILABLE











	QC12Y- 12×2500	QC12Y- 12×3200	QC12Y- 12×4000	QC12Y- 12×6000	QC12Y- 16×2500	QC12Y- 16×3200	QC12Y- 16×4000	QC12Y- 16×6000	QC12Y- 20×2500	QC12Y- 20×3200	QC12Y- 20×6000	QC12Y- 25×2500	QC12Y- 25×3200	QC12Y- 32×2500	QC12Y- 32×3200	QC12Y- 40×2500
Model	12×2500	12×3200	12×4000	12×6000	16×2500	16×3200	16×4000	16×6000	20×2500	20×3200	20×6000	25×2500	25×3200	32×2500	32×3200	40×2500
Shearing Angle	2°	2°	1°54′	2°	2°9′	2°	2°	2°	2°30′	2°30′	2°30′	2°30′	3°	3°30′	3°30′	3°30′
Strokes p/m	≥14	≥12	≥10	≥6	≥13	≥11	≥10	≥5	≥8	≥7	≥5	≥5	≥5	≥5	≥4	≥3
Backgauge adj.	20-800	20-800	20-800	20-1000	20-800	20-800	20-1000	20-1000	20-1000	20-1000	20-1200	20-1000	20-1000	20-1200	20-1200	20-1200
Throat	300	300	300	320	315	320	320	320	325	320	150	325	325	350	350	200
Motor	22	22	22	30	30	30	30	45	30	30	55	37	37	45	45	45
Weight	8110	10600	13800	38000	10900	14300	19700	44000	16500	22500	51000	20000	27000	32500	42100	48000
Dimension	3240× 2030× 1840	4030× 2100× 1940	4750× 2270× 2000	6900× 2800× 2500	3280× 2240× 2000	4000× 2200× 2100	4800× 2490× 2300	7100× 2900× 2650	3360× 2545× 2250	4190× 2695× 2300	7100× 3500× 3050	3420× 2600× 2800	4130× 3100× 2800	3550× 3100× 2800	4335× 3300× 3280	3600× 3450× 3200



www.thmachinetools.co.za